

View Online at <https://aerobasegroup.com/nsn/5985-00-994-3682>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches first flange

Flange Inside Height:

0.628 inches first flange

Flange Outside Width:

1.860 inches first flange and 1.890 inches first flange

Flange Outside Height:

1.860 inches first flange and 1.890 inches first flange

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.08

Adapter Length:

3.750 inches

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Special Features:

Frequency range 8.2 to 12.4 khz; waveguide size tapers from rg-51/u to rg-52/u

Material:

Copper alloy all tubing segment and flange or aluminum all tubing segment and flange

Surface Treatment:

Chromate zinc all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces

Style Designator:

Waveguide to waveguide

Specification Data:

18876-10667940 manufacturers specification control

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0