NSN 5985-00-996-5204

Variable Attenuator - Page 1 of 2

Application Design:

Cylindrical w/side terminals

Audio

Body Style:

Overall Length: 4.750 inches Body Diameter: 2.344 inches



View Online at https://aerobasegroup.com/nsn/5985-00-996-5204

Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
3.812 inches
Schematic Diagram Designator:
"t"
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
500.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+10.0/+100.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
Attenuation Per Step In Decibels: 10.0
10.0
10.0 Mounting Facility Type And Quantity:
10.0 Mounting Facility Type And Quantity: 2 threaded hole
10.0 Mounting Facility Type And Quantity: 2 threaded hole Frequency Range:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity: 32 per inch
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Two position in-line
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 kilohertz and 50.000 kilohertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Two position in-line Shaft Type:

NSN 5985-00-996-5204

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Reference Number Differentiating Characteristics:
Quality controlled for polaris
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0