NSN 5985-00-996-5205

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-996-5205

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
3.000 inches
Overall Width:
2.344 inches
Body Diameter:
Between 2.250 inches and 2.312 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
2.062 inches
Schematic Diagram Designator:
"t"
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
0.5 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 50.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.10/+0.10
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-00-996-5205

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Reference Number Differentiating Characteristics:
Quality controlled for polaris
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A223a0