

View Online at <https://aerobasegroup.com/nsn/5985-01-004-6180>

**Application Design:**

Transmission line

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Coaxial Connector Series Designation:**

Bnc

**Power Rating:**

3.0 watts average

**Mounting Facility Screw Thread Series Designator:**

Unc

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.2

**Overall Attenuation Range In Decibels:**

+0.0/+100.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

10

**Attenuation Per Step In Decibels:**

10.0

**Mounting Facility Type And Quantity:**

4 threaded hole

**Frequency Range:**

Between 0.000 gigahertz and 2.000 gigahertz

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 knob

**Mounting Facility Screw Thread Diameter:**

0.138 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A223a0