# NSN 5985-01-005-5081

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-005-5081

### **Cross Sectional Shape:** Internal, rectangular external, rectangular **Thread Class:** 2b first flange all connection facilities Thread Direction: Right-hand first flange all connection facilities Bend Angle In Deg: 90.0 single bend e-plane **Tubing Wall Construction Style:** Interlocked single tubing segment Flange Quantity: Flange Inside Width: 1.003 inches second flange Flange Inside Height: 0.505 inches second flange Flange Outside Width: 1.625 inches second flange Flange Outside Height: 1.625 inches first flange Flange Inside Diameter: 1.003 inches first flange Flange Depth: 0.438 inches second flange Flange Connecting Hole Diameter: 0.169 inches second flange all connection facilities **Voltage Standing Wave Ratio:** 1.06 **Insertion Loss In Decibels:** 0.10 Waveguide Outside Width: 1.000 inches **Thread Size:** 0.112 inches first flange all connection facilities Waveguide Inside Width: 0.900 inches Waveguide Inside Height: 0.400 inches Waveguide Outside Height: 0.500 inches Waveguide Longer Offset Distance: 2.812 inches

2

## NSN 5985-01-005-5081

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

#### Flange Style:

Cover type second flange

### Waveguide Offset Distance:

1.520 inches

Flexibility:

Flexible single tubing segment

#### Material:

Copper alloy single tubing segment

#### Surface Treatment:

Oxide film single tubing segment all surfaces

Style Designator:

Bend type

#### **Thread Series Designator:**

Unc first flange all connection facilities

#### Shelf Life:

N/a

--

#### Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0