NSN 5985-01-005-5095

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-005-5095 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Silver plated, qq-s-365 **Overall Length:** 2.200 inches **Overall Diameter:** 0.600 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** Modulator-oscillator gp 1175 daul exciter model om-34/frc-123 **Voltage Standing Wave Ratio:** 1.20 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Tnc **Power Rating:** 2.0 watts average and 3.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 2.0 **Attenuation Accuracy Reference Frequency:** 2.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female output and male input **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 gigahertz and 2.000 gigahertz **Precious Material And Location:**

Body surface silver

NSN 5985-01-005-5095 Fixed Attenuator - Page 2 of 2



Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000