NSN 5985-01-006-7917

Electrical Dummy Load - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-006-7917

Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Overall Length: 0.688 inches Overall Diameter: 0.375 inches Frequency Range Rating: +0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator: Coaxial mounted
Overall Length: 0.688 inches Overall Diameter: 0.375 inches Frequency Range Rating: +0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Overall Diameter: 0.375 inches Frequency Range Rating: +0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Overall Diameter: 0.375 inches Frequency Range Rating: +0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
0.375 inches Frequency Range Rating: +0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Frequency Range Rating: +0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
+0.000/+18.000 gigahertz Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Voltage Standing Wave Ratio: 1.15 and 1.20 Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Coaxial Connector Series Designation: Sma Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Connector End Design: Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Male Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Power Rating: 0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
0.500 watts average Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Voltage Standing Wave Ratio Frequency Range: +0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
+0.000/+10.000 gigahertz and +10.000/+18.000 gigahertz Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Termination Type: Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Connection coaxial Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Operating Position: All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
All positions Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Cooling Method: Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Self-cooled Special Features: W/2.000 in. Lg chain Style Designator:
Special Features: W/2.000 in. Lg chain Style Designator:
W/2.000 in. Lg chain Style Designator:
Style Designator:
Coaxial mounted
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A19800