

View Online at <https://aerobasegroup.com/nsn/5985-01-007-2311>

Body Style:

Irregular

Overall Length:

3.710 inches

Overall Height:

3.500 inches

Overall Width:

2.800 inches

Frequency Rating:

4.0 gigahertz 2nd frequency insertion loss reference and 8.0 gigahertz 2nd frequency insertion loss reference

Unthreaded Mounting Hole Diameter:

0.187 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

3.000 inches single mounting facility pattern

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 3rd

Insertion Loss In Decibels:

0.50 3rd

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

80.0 1st

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.170 dc

Actuator Voltage In Volts:

Between 20.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

5

Coupling Position Quantity:

6

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Special Features:

Operational life 100, 000 operations

Material:

Copper connecto (s)

Surface Treatment:

Paint cover all surfaces

Terminal Type And Quantity:

6 receptacle, coaxial and 1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0