

View Online at <https://aerobasegroup.com/nsn/5985-01-008-3578>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.362 inches second flange and 0.364 inches second flange

Flange Inside Height:

0.222 inches second flange and 0.224 inches second flange

Flange Outside Width:

0.735 inches first flange and 0.765 inches first flange

Flange Outside Height:

0.735 inches first flange and 0.765 inches first flange

Flange Inside Diameter:

0.485 inches first flange and 0.515 inches first flange

Flange Depth:

0.195 inches first flange and 0.225 inches first flange

Flange Connecting Hole Diameter:

0.116 inches second flange all connection facilities and 0.118 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.50

Waveguide Outside Width:

Between 0.358 inches and 0.362 inches

Thread Size:

0.112 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.279 inches and 0.282 inches

Waveguide Inside Height:

Between 0.139 inches and 0.142 inches

Waveguide Outside Height:

Between 0.218 inches and 0.222 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

5.020 inches

Flexibility:

Flexible single tubing segment

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0