NSN 5985-01-009-2284

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-009-2284

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

NSN 5985-01-009-2284

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity: 4 unthreaded hole second flange all connection facilities Flange Style: Choke type first flange **Waveguide Center To Center Distance:** 17.680 inches **Waveguide Height:** 1.720 inches Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange **Surface Treatment:** Chromate all tubing segment and flange outside surfaces **Style Designator:** Double bend type **Thread Series Designator:** Unc first flange all connection facilities **Specification Data:** 36659-673072 manufacturers specification control Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

Fiig: A073a0