NSN 5985-01-009-3678

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-009-3678 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 7.062 inches **Overall Diameter:** 1.625 inches **Voltage Standing Wave Ratio:** 1.20 and 1.30 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 50.0 watts average and 2.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+3.0 gigahertz and +3.0/+5.0 gigahertz **Attenuation Accuracy Reference Frequency:** 5.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Temperature Sensitivity Attenuation In Decibels: Connection Type Per Function:** Female output and male input **Unpackaged Unit Weight:** 15.500 ounces **Mounting Method:** Connector **Terminal Type And Quantity:**

2 connector
Frequency Range:

Between 0.000 gigahertz and 5.000 gigahertz

NSN 5985-01-009-3678

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A20000