# NSN 5985-01-009-3678

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-009-3678

## Application Design:

Transmission line

#### **Body Material:**

Metal

### Body Style:

Err-090

#### **Body Surface Treatment:**

Any acceptable

#### **Overall Length:**

7.062 inches

#### **Overall Diameter:**

1.625 inches

#### Voltage Standing Wave Ratio:

1.20 and 1.30

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Ν

#### **Power Rating:**

50.0 watts average and 2.0 kilowatts peak

#### **Rf Signal Attenuation In Decibels:**

10.0

#### Voltage Standing Wave Ratio Frequency Range:

+0.0/+3.0 gigahertz and +3.0/+5.0 gigahertz

#### Attenuation Accuracy Reference Frequency:

5.0 gigahertz

#### Attenuation Accuracy In Decibels:

-0.50/+0.50

#### Temperature Sensitivity Attenuation In Decibels:

0.0010

## **Connection Type Per Function:**

Female output and male input

## Unpackaged Unit Weight:

15.500 ounces

## Mounting Method:

Connector

## Terminal Type And Quantity:

2 connector

## Frequency Range:

Between 0.000 gigahertz and 5.000 gigahertz

# NSN 5985-01-009-3678

Fixed Attenuator - Page 2 of 2



**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A20000