NSN 5985-01-013-3830

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-013-3830

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Any acceptable
Overall Length:
1.140 inches
Overall Diameter:
0.340 inches
Voltage Standing Wave Ratio:
1.20 and 1.30 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Rf Signal Attenuation In Decibels:
18.0
Walter Committee War Built Francisco Brancis
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz Fsc Application Data: Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure: Demilitarization: