NSN 5985-01-013-6209

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-013-6209

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
6.060 inches
Bolt Circle Diameter:
5.375 inches
Overall Height:
2.250 inches
Overall Width:
5.000 inches
Scale Linearity:
Linear
Scale Division Quantity:
19
Operating Tempurature Range:
+0.0/+60.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
8 threaded hole
Frequency Range:
Between 750.000 megahertz and 850.000 megahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:

Three position circular

NSN 5985-01-013-6209

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.164 inches

Terminal Type And Quantity:

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A223a0