## NSN 5985-01-013-8486

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-013-8486 **Application Design:** Transmission line **Body Material:** Any acceptable **Body Style:** Rectangular, terminal/terminals on one surface **Body Surface Treatment:** Any acceptable **Overall Length:** Between 0.480 inches and 0.520 inches **Overall Height:** 0.959 inches **Overall Width:** Between 0.480 inches and 0.520 inches **Body Height:** Between 0.390 inches and 0.430 inches **Operating Tempurature Range:** +0.0/+55.0 degrees celsius **Voltage Standing Wave Ratio:** 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Rf Signal Attenuation In Decibels:** 15.0 **Voltage Standing Wave Ratio Frequency Range:** +45.0/+75.0 megahertz **Center To Center Distance Between First And Second Terminals:** 0.125 inches **Center To Center Distance Between Second And Third Terminals:** 0.094 inches **Center To Center Distance Between Third And Fourth Terminals:** 0.156 inches

**Attenuation Accuracy In Decibels:** -0.30/+0.30 **Mounting Method:** Plug-in **Terminal Type And Quantity:** 4 pin Frequency Range:

Between 45.000 megahertz and 75.000 megahertz

## NSN 5985-01-013-8486

Fixed Attenuator - Page 2 of 2



Measurements center to center for pins 2 to 3 and 3 to 4 are vertical

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000