## NSN 5985-01-013-8488

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-013-8488 **Application Design:** Transmission line **Body Material:** Any acceptable **Body Style:** Rectangular, terminal/terminals on one surface **Body Surface Treatment:** Any acceptable **Overall Length:** Between 0.480 inches and 0.520 inches **Overall Height:** 0.959 inches **Overall Width:** Between 0.480 inches and 0.520 inches **Body Height:** Between 0.390 inches and 0.430 inches **Operating Tempurature Range:** +0.0/+55.0 degrees celsius **Voltage Standing Wave Ratio:** 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Rf Signal Attenuation In Decibels:** 8.0 **Voltage Standing Wave Ratio Frequency Range:** +45.0/+75.0 megahertz **Center To Center Distance Between First And Second Terminals:** 0.125 inches

**Center To Center Distance Between Second And Third Terminals:** 

0.094 inches

**Center To Center Distance Between Third And Fourth Terminals:** 

0.156 inches

**Attenuation Accuracy In Decibels:** 

-0.20/+0.20

**Mounting Method:** 

Plug-in

**Terminal Type And Quantity:** 

4 pin

Frequency Range:

Between 45.000 megahertz and 75.000 megahertz

## NSN 5985-01-013-8488

Fixed Attenuator - Page 2 of 2



Special	Features:
---------	-----------

Center to center measurements for pins 2 to 3 and 3 to 4 are vertical

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000