NSN 5985-01-014-3463

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-014-3463

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

1b round, terminal/terminals in opposite surface

Body Surface Treatment:

Passivated

Overall Length:

3.040 inches

Overall Diameter:

0.840 inches

Operating Tempurature Range:

+85.0/+125.0 degrees celsius

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Ν

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

12.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

Frequency Sensitivity Attenuation In Decibels:

0.30

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5985-01-014-3463

Fixed Attenuator - Page 2 of 2

Fiig: A20000

