NSN 5985-01-014-3464



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-014-3464 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 2.680 inches **Overall Diameter:** 0.840 inches **Operating Tempurature Range:** +85.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 and 1.40 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 40.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy In Decibels:** -1.00/+1.00 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life:

Unit Of Measure:

N/a

NSN 5985-01-014-3464

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000