NSN 5985-01-015-2356

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-015-2356

Application Design:
Transmission line
Body Material: Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Bright alloy
Overall Length:
1.234 inches
Overall Diameter:
0.375 inches
Voltage Standing Wave Ratio:
1.15 and 1.30 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Npm
Power Rating:
2.0 watts average and 0.2 kilowatts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.90/+0.90
Frequency Sensitivity Attenuation In Decibels:
0.90
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-015-2356

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000