NSN 5985-01-015-2362

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-015-2362
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
Between 1.683 inches and 1.723 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.173 inches and 1.203 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 0.673 inches and 0.703 inches
Overall Height:
1.100 inches
Overall Width:
2.100 inches
Mounting Slot Length:
0.250 inches
Operating Tempurature Range:
+0.0/+55.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 45.000 megahertz and 75.000 megahertz
Mounting Thread Quantity:
40 per inch
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.112 inches
Fsc Application Data:
Pallet, aircraft maintenance

N/a

Shelf Life:

NSN 5985-01-015-2362

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0