NSN 5985-01-015-5912

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-015-5912

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Rectangular, terminal/terminals on opposite surfaces |
| Body Surface Treatment: |
| Enamel |
| Overall Length: |
| 5.187 inches |
| Overall Height: |
| 1.625 inches |
| Overall Width: |
| 1.250 inches |
| Voltage Standing Wave Ratio: |
| 1.10 and 1.15 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 40.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+500.0 megahertz and +0.5/+1.0 gigahertz |
| Attenuation Accuracy Reference Frequency: |
| 500.0 megahertz |
| Attenuation Accuracy In Decibels: |
| -0.50/+0.50 |
| Connection Type Per Function: |
| Female input and female output |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 1.000 gigahertz |
| Special Features: |
| Wattage rating given when bolted to 0.125 in. Thk. Aluminum panel |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5985-01-015-5912

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000