NSN 5985-01-015-5913



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-015-5913 **Application Design:** Transmission line **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Enamel **Overall Length:** 5.187 inches **Overall Height:** 1.625 inches **Overall Width:** 1.250 inches **Voltage Standing Wave Ratio:** 1.10 and 1.15 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 40.0 watts average **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+500.0 megahertz and +0.5/+1.0 gigahertz **Attenuation Accuracy Reference Frequency:** 500.0 megahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and female output **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 1.000 gigahertz **Special Features:**

Wattage rating given when bolted to 0.125 in. Thk. Aluminum panel Shelf Life: N/a **Unit Of Measure:**

NSN 5985-01-015-5913

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000