## NSN 5985-01-016-2579

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-016-2579

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
1.781 inches
Overall Width:
1.258 inches
Body Diameter:
0.938 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
0.875 inches
Body Length:
0.906 inches
Schematic Diagram Designator:
Balanced ladder
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Power Rating:
4.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+50.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Impedance Rating In Ohms:
600.0 input-output

## NSN 5985-01-016-2579

Variable Attenuator - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0