NSN 5985-01-016-6372

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-016-6372

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
8.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.250 inches
Overall Height:
Between 4.360 inches and 4.860 inches
Overall Width:
1.000 inches
Scale Linearity:
Linear
Scale Division Quantity:
40
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.812 inches
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.7
Overall Attenuation Range In Decibels:
+0.0/+80.0
Attenuation Accuracy Reference Frequency:
2.2525 gigahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Overall Attenuation Accuracy In Decibels:
-2.50/+2.50
Mounting Thread Quantity:

32 per inch

NSN 5985-01-016-6372

Variable Attenuator - Page 2 of 2

Fiig: A223a0



Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
1 connector, coaxial, male and 1 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No