Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-017-1279

# Application Design:

Transmission line

**Body Material:** 

Steel, stainless

# Body Style:

Err-090

#### Body Surface Treatment:

Any acceptable

#### **Overall Length:**

2.969 inches

#### **Overall Diameter:**

0.625 inches

#### Voltage Standing Wave Ratio:

1.20 and 1.25

**Coaxial Connector Series Designation:** 

# Power Rating:

2.0 watts average and 300.0 watts peak

# **Rf Signal Attenuation In Decibels:**

40.0

Ν

# Voltage Standing Wave Ratio Frequency Range:

+0.0/+6.0 gigahertz and +6.0/+12.4 gigahertz

# Attenuation Accuracy In Decibels:

-1.25/+1.25

## Temperature Sensitivity Attenuation In Decibels:

0.0001

#### **Connection Type Per Function:**

Female input and male output

#### Mounting Method:

Connector

## **Terminal Type And Quantity:**

2 connector

## Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# Fiig:

A20000