# NSN 5985-01-020-1062

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-020-1062

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b first flange all connection facilities

#### **Thread Direction:**

Right-hand first flange all connection facilities

#### Bend Angle In Deg:

90.0 single bend h-plane

#### Tubing Wall Construction Style:

Seamless single tubing segment

#### Flange Quantity:

2

#### Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

#### Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

#### Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

#### Flange Outside Height:

1.610 inches second flange and 1.640 inches second flange

#### Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

#### Flange Depth:

0.423 inches second flange and 0.463 inches second flange

#### Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

#### Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

#### Thread Size:

0.164 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

#### Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

#### Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

#### Waveguide Longer Offset Distance:

3.000 inches

#### Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

#### Flange Style:

Cover type second flange

# NSN 5985-01-020-1062

Waveguide Assembly - Page 2 of 2



# Waveguide Offset Distance:

3.000 inches

Flexibility:

Rigid single tubing segment

### Material:

Copper alloy all tubing segment and flange

# Surface Treatment:

Enamel all tubing segment and flange outside surfaces

#### Style Designator:

Bend type

## **Thread Series Designator:**

Unc first flange all connection facilities

### **Fsc Application Data:**

Antennas, waveguides, and related equipment

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A073a0