## NSN 5985-01-020-6049

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-020-6049

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.360 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.802 inches and 1.822 inches
Overall Height:
Between 0.970 inches and 1.030 inches
Overall Width:
4.250 inches
Shaft Length:
2.840 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.240 inches and 1.260 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 60.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.5/+10.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Four position rectangular
Shaft Type:
Round

## NSN 5985-01-020-6049

Variable Attenuator - Page 2 of 2



## **Mounting Facility Screw Thread Diameter:**

0.138 inches

Impedance Rating In Ohms:

50.0 input-output

**Terminal Type And Quantity:** 

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0