NSN 5985-01-021-1595



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-021-1595 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 2.656 inches **Overall Diameter:** 0.812 inches **Voltage Standing Wave Ratio:** 1.15 and 1.30 and 1.40 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy Reference Frequency:** 18.0 gigahertz **Attenuation Accuracy In Decibels:**

-0.70/+0.70

Connection Type Per Function:

Female input and male output

Unpackaged Unit Weight:

2.700 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-021-1595

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000