## NSN 5985-01-021-7026



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-021-7026 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 6.620 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.414 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.414 inches **Overall Height:** 2.500 inches **Overall Width:** 2.750 inches **Mounting Hole/stud Quantity: Unthreaded Mounting Hole Diameter:** 0.138 inches **Voltage Standing Wave Ratio:** 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν

**Power Rating:** 

50.0 watts average

Rf Signal Attenuation In Decibels:

40.0

**Mounting Method:** 

Unthreaded hole

**Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 400.000 megahertz

Shelf Life:

N/a

## NSN 5985-01-021-7026

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000