NSN 5985-01-023-2669

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-023-2669

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.820 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.950 inches
Overall Height:
1.000 inches
Overall Width:
0.500 inches
Scale Linearity:
Linear
Unthreaded Mounting Hole Diameter:
0.125 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 10.0 watts peak
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 16.300 gigahertz and 17.300 gigahertz
Adjustment Device Type And Quantity:
1 motor
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
90.0 input-output
Terminal Type And Quantity:

3 tab, solder lug

NSN 5985-01-023-2669

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0