NSN 5985-01-025-7235

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-025-7235

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 first bend e-plane

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches first flange and 0.624 inches first flange

Flange Inside Height:

0.309 inches first flange and 0.313 inches first flange

Flange Outside Width:

1.297 inches first flange and 1.327 inches first flange

Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Waveguide Center To Center Distance:

Between 6.280 inches and 6.340 inches

Waveguide Height:

Between 6.970 inches and 7.030 inches

NSN 5985-01-025-7235

Waveguide Assembly - Page 2 of 2

A073a0



Flexibility:
Rigid all tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Chromate all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces
Style Designator:
Double bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: