NSN 5985-01-025-7283

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-025-7283

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
1.570 inches
Overall Diameter:
0.450 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.35 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
14.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
0.350 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Retween 0 000 hertz and 18 000 gigahertz

NSN 5985-01-025-7283

Fixed Attenuator - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000