

View Online at <https://aerobasegroup.com/nsn/5985-01-025-7286>

Application Design:

Transmission line

Body Material:

Steel, corrosion resisting

Body Style:

1b round, terminal/terminals in opposite surface

Body Surface Treatment:

Passivated, qq-p-35

Overall Length:

1.200 inches

Overall Diameter:

0.360 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.20 and 1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

20.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000