## NSN 5985-01-025-7286



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-025-7286 **Application Design:** Transmission line **Body Material:** Steel, corrosion resisting **Body Style:** 1b round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated, qq-p-35 **Overall Length:** 1.200 inches **Overall Diameter:** 0.360 inches **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 20.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz

Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5985-01-025-7286

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000