

View Online at <https://aerobasegroup.com/nsn/5985-01-026-2074>

Body Style:

Rectangular

Overall Length:

2.450 inches

Overall Height:

2.160 inches

Overall Width:

1.650 inches

Frequency Rating:

0.0 gigahertz single frequency operating and 12.0 gigahertz single frequency operating

Unthreaded Mounting Hole Diameter:

Between 0.144 inches and 0.154 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.082 inches single mounting facility pattern and 1.098 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.772 inches single mounting facility pattern and 1.788 inches single mounting facility pattern

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Maximum Operating Altitude Rating:

10000.0 feet

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

12.0 dc

Actuator Voltage In Volts:

Between 18.0 and 32.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Special Features:

Fungus inert materials

Material:

Aluminum alloy body

Surface Treatment:

Paint body outside surfaces

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0