

View Online at <https://aerobasegroup.com/nsn/5985-01-026-7065>

**Application Design:**

Transmission line

**Body Style:**

Coaxial type

**Overall Length:**

2.625 inches

**Overall Height:**

2.125 inches

**Overall Width:**

1.375 inches

**Voltage Standing Wave Ratio:**

1.20 and 1.30

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

0.25 watts average and 250.00 watts peak

**Mounting Facility Screw Thread Series Designator:**

Unef

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.5

**Overall Attenuation Range In Decibels:**

+0.0/+60.0

**Attenuation Accuracy Reference Frequency:**

500.0 megahertz

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

10

**Attenuation Per Step In Decibels:**

6.0

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Frequency Range:**

Between 0.000 hertz and 2000.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 knob

**Mounting Facility Screw Thread Diameter:**

0.375 inches

**Impedance Rating In Ohms:**

50.0 input-output

**Terminal Type And Quantity:**

2 connector, coaxial, female

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0