# NSN 5985-01-026-7065

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-026-7065

view Online at https://aerobasegroup.com/nsi//3505-01-020-/000
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.625 inches
Overall Height:
2.125 inches
Overall Width:
1.375 inches
Voltage Standing Wave Ratio:
1.20 and 1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
0.25 watts average and 250.00 watts peak
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Accuracy Reference Frequency:
500.0 megahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
6.0
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 hertz and 2000.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Screw Thread Diameter:
0.375 inches

## NSN 5985-01-026-7065

Variable Attenuator - Page 2 of 2



#### Impedance Rating In Ohms:

50.0 input-output

### Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

Yes - demil/mli

Fiig:

A223a0