NSN 5985-01-027-8271

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-027-8271

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
3.000 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N and sc
Power Rating:
5.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
6.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz

NSN 5985-01-027-8271

Fixed Attenuator - Page 2 of 2



Fsc Application Data	Fsc Appl	ication	Data
----------------------	----------	---------	------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A20000