NSN 5985-01-028-9247

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-01-028-9247

Transmission line
Body Material:
Any acceptable
Body Style:
Rectangular terminal/terminals on three surfaces
Body Surface Treatment:
Gold plated
Overall Length:
0.647 inches
Overall Height:
0.035 inches
Overall Width:
0.374 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Rf Signal Attenuation In Decibels:
3.0
Attenuation Accuracy Reference Frequency:
1.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Unpackaged Unit Weight:
0.003 pounds
Mounting Method:
Printed circuit
Terminal Type And Quantity:
Terminal Type And Quantity: 3 ribbon
3 ribbon
3 ribbon Frequency Range:
3 ribbon Frequency Range: Between 0.000 hertz and 18.000 gigahertz
3 ribbon Frequency Range: Between 0.000 hertz and 18.000 gigahertz Precious Material And Location:
3 ribbon Frequency Range: Between 0.000 hertz and 18.000 gigahertz Precious Material And Location: External surfaces gold
3 ribbon Frequency Range: Between 0.000 hertz and 18.000 gigahertz Precious Material And Location: External surfaces gold Precious Material:
3 ribbon Frequency Range: Between 0.000 hertz and 18.000 gigahertz Precious Material And Location: External surfaces gold Precious Material: Gold

N/a

NSN 5985-01-028-9247

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000