## NSN 5985-01-029-5996

Fixed Attenuator - Page 1 of 2

**Application Design:** 



View Online at https://aerobasegroup.com/nsn/5985-01-029-5996

Transmission line				
Body Material:				
Any acceptable				
Body Style:				
Rectangular terminal/terminals on three surfaces				
Body Surface Treatment:				
Any acceptable				
Overall Length:				
0.805 inches				
Overall Height:				
0.040 inches				
Overall Width:				
0.490 inches				
Operating Tempurature Range:				
-55.0/+150.0 degrees celsius				
Voltage Standing Wave Ratio:				
1.30				
Input Impedance Rating In Ohms:				
50.0				
Output Impedance Rating In Ohms:				
50.0				
Power Rating:				
500.0 milliwatts average				
Rf Signal Attenuation In Decibels:				
20.0				
Voltage Standing Wave Ratio Frequency Range:				
+55.0/+470.0 megahertz				
Attenuation Accuracy Reference Frequency:				
470.0 megahertz				
Attenuation Accuracy In Decibels:				
-0.50/+0.50				
Mounting Method:				
Printed circuit				
Terminal Type And Quantity:				
31.				
3 ribbon				
3 ribbon				
3 ribbon Frequency Range:				
3 ribbon  Frequency Range:  Between 55.000 megahertz and 470.000 megahertz				
3 ribbon  Frequency Range:  Between 55.000 megahertz and 470.000 megahertz  Precious Material And Location:				

## NSN 5985-01-029-5996

Fixed Attenuator - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000