NSN 5985-01-030-2766

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-030-2766

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
6.500 inches
Overall Height:
4.000 inches
Overall Width:
3.880 inches
Operating Tempurature Range:
-25.0/+150.0 degrees fahrenheit
Voltage Standing Wave Ratio:
1.25
Power Rating:
3.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Waveguide Flange Type:
Choke
Waveguide Flange Designation:
Ug-137/bu
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 7.900 gigahertz and 8.400 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 motor
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.164 inches
Terminal Type And Quantity:

2 flange

NSN 5985-01-030-2766

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0