NSN 5985-01-030-3095

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-030-3095

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

2.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.844 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.094 inches

Overall Height:

2.000 inches

Overall Width:

0.500 inches

Operating Tempurature Range:

-65.0/+150.0 degrees fahrenheit

Voltage Standing Wave Ratio:

```
1.20
```

Coaxial Connector Series Designation:

Sma

Power Rating:

5.0 watts average and 3.0 kilowatts peak

Mounting Facility Screw Thread Series Designator:

Unc

Overall Attenuation Range In Decibels:

+14.0/+17.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 1615.000 megahertz and 1715.000 megahertz

Mounting Thread Quantity:

40 per inch

Adjustment Device Type And Quantity:

1 slotted screw

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.112 inches

Terminal Type And Quantity:

2 connector, coaxial, female

NSN 5985-01-030-3095

Variable Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0

