## NSN 5985-01-030-7819

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-030-7819 **Application Design:** Transmission line **Body Material:** Any acceptable **Body Style:** Err-090 **Overall Length:** 1.210 inches **Overall Diameter:** 0.357 inches **Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.14 and 1.23 and 1.27 and 1.35 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 500.0 watts peak **Rf Signal Attenuation In Decibels:** 6.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+10.0 gigahertz and +10.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5985-01-030-7819

Fixed Attenuator - Page 2 of 2



Fiig:

A20000