NSN 5985-01-030-9979

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-030-9979

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

4

Flange Inside Width:

1.253 inches first flange

Flange Inside Height:

0.628 inches first flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Depth:

0.625 inches second flange

Flange Connecting Hole Diameter:

0.169 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.25

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Waveguide Longer Offset Distance:

3.030 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Waveguide Width:

3.905 inches

NSN 5985-01-030-9979 Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type first flange
Waveguide Length:
4.590 inches
Waveguide Height:
2.378 inches
Flexibility:
Rigid all tubing segment
Material:
Copper alloy all flange
Surface Treatment:
Gold all flange all surfaces
Style Designator:
Tee, shunt type
Thread Series Designator:
Unc second flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0