NSN 5985-01-031-5975

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-031-5975
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
1.140 inches
Overall Diameter:
0.312 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts peak
Rf Signal Attenuation In Decibels:
5.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.0 gigahertz
Attenuation Accuracy Reference Frequency:
2.0 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector

Frequency Range:

2 connector

Between 0.000 hertz and 2.000 gigahertz

Terminal Type And Quantity:

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-031-5975

Fixed Attenuator - Page 2 of 2



he			

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000