NSN 5985-01-032-1562

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:

Body Surface Treatment:

Err-090

Passivated



View Online at https://aerobasegroup.com/nsn/5985-01-032-1562

Overall Length:
1.240 inches
Overall Diameter:
0.390 inches
Voltage Standing Wave Ratio:
1.15 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Osm
Power Rating:
2.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz
Attenuation Accuracy Reference Frequency:
12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.75/+0.75
Unpackaged Unit Weight:
0.300 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Antennas, waveguides, and related equipment Shelf Life:

NSN 5985-01-032-1562

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000