NSN 5985-01-032-4048

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-032-4048

Cross Sectional Shape: Internal, rectangular external, rectangular **Thread Class:** 2b second flange single connection facility Thread Direction: Right-hand second flange single connection facility **Bend Angle In Deg:** 90.0 single bend e-plane **Tubing Wall Construction Style:** Seamless single tubing segment Flange Quantity: Flange Inside Width: 1.253 inches first flange Flange Inside Height: 0.628 inches first flange Flange Outside Width: 1.875 inches second flange Flange Outside Height: 1.875 inches second flange Flange Depth: 0.625 inches second flange Flange Connecting Hole Diameter: 0.196 inches first flange single connection facility **Voltage Standing Wave Ratio:** 1.15 Maximum Operating Pressure: 1.0 pounds per square inch gage Waveguide Outside Width: 1.250 inches **Thread Size:** 0.164 inches second flange single connection facility Waveguide Inside Width: 1.122 inches Waveguide Inside Height: 0.497 inches Waveguide Outside Height: 0.625 inches Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

2

Cover type first flange

NSN 5985-01-032-4048

Waveguide Assembly - Page 2 of 2



Waveguide Center To Center Distance:

15.888 inches

Waveguide Height:

4.750 inches

Special Features:

No inside surface treatment to be applied to tubing or flange

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all flange

Surface Treatment:

Enamel all flange outside surfaces

Style Designator:

Double bend type

Thread Series Designator:

Unc second flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0