NSN 5985-01-032-4048

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-032-4048

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches first flange

Flange Inside Height:

0.628 inches first flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Depth:

0.625 inches second flange

Flange Connecting Hole Diameter:

0.196 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.15

Maximum Operating Pressure:

1.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

Cover type first flange

NSN 5985-01-032-4048 Waveguide Assembly - Page 2 of 2



Waveguide Center To Center Distance:
15.888 inches
Waveguide Height:
4.750 inches
Special Features:
No inside surface treatment to be applied to tubing or flange
Flexibility:
Rigid single tubing segment
Material:
Copper alloy all flange
Surface Treatment:
Enamel all flange outside surfaces
Style Designator:
Double bend type
Thread Series Designator:
Unc second flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0