NSN 5985-01-032-4061

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-032-4061

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Coaxial type
Overall Length:
2.740 inches
Overall Height:
1.735 inches
Overall Width:
1.310 inches
Mounting Slot Width:
0.172 inches
Mounting Slot Length:
0.297 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.430 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.25
Coaxial Connector Series Designation:
Sma
Power Rating:
250.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Accuracy Reference Frequency:
2.0 gigahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:

1 bracket

NSN 5985-01-032-4061

Variable Attenuator - Page 2 of 2



Freq	uency	Range:

Between 0.000 hertz and 0.500 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Adjustment Device Type And Quantity:

1 shaft

Shaft Type:

Round

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A223a0