NSN 5985-01-032-6620

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-032-6620

Application Design:
Transmission line
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Overall Length:
1.562 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.656 inches
Overall Height:
1.250 inches
Overall Width:
0.625 inches
Mounting Hole/stud Quantity:
2
Body Length:
0.812 inches
Unthreaded Mounting Hole Diameter:
0.101 inches
Voltage Standing Wave Ratio:
2.00
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Sma Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels: 40.0
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range:
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function:
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output Mounting Method:
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output Mounting Method: Unthreaded hole
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output Mounting Method: Unthreaded hole Terminal Type And Quantity:
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output Mounting Method: Unthreaded hole Terminal Type And Quantity: 4 connector
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output Mounting Method: Unthreaded hole Terminal Type And Quantity: 4 connector Frequency Range:
Rf Signal Attenuation In Decibels: 40.0 Voltage Standing Wave Ratio Frequency Range: +0.4/+12.4 gigahertz Connection Type Per Function: Female input and female output Mounting Method: Unthreaded hole Terminal Type And Quantity: 4 connector Frequency Range: Between 0.400 gigahertz and 12.400 gigahertz

--

NSN 5985-01-032-6620

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000